




HabiStat™ NOVA ACTIVATION SYSTEM

INSTALLTION AND SET UP INSTRUCTIONS



- A: Pump rate adjustment
- B: Power on / off
- C: Lock. Push and hold to lock. Push and hold to unlock.

1. Install Panel in appropriate location.
2. Attach incoming water source.
3. Attach outgoing line (with shut off).
4. Verify water flow rates – 7 gpm.
 - a. Adjust water regulator as required.
5. Place chemical draw tubes in appropriate containers.
6. Never mix undiluted Activator and Base together outside of the Activation chamber.
With system charged with water, set pump rate to 100 and fill the activation chamber.
7. Set desired PPM based on chart below.
8. Run treated solution into a pail and verify ORP and Active PPM.
9. Check ORP and ppm regularly.

HABISTAT™ / NOVA™ ACTIVATION SYSTEM*		
METER SETTINGS	=	1 PULSE PER GALLON
CONTROLLER SETTING:		COUNT = 1, TIME = 7
PUMP SETTING	ACTIVE PPM	WATER REGULATOR MAX FLOW RATE
100	200	7 gpm
50	100	14 gpm
25	50	28 gpm

*All activation done under water pressure. For best results, use water hardness of less than 5 gpg. Source water treated with H₂O₂ may affect ORP levels.

For more information, call Acepsis™ or your local representative.



ACEPSIS™, LLC is an animal health based company that is focused on the development of state-of-the-art animal hygiene technologies. Our Company's mission is to apply innovative animal hygiene technologies into the agricultural and veterinary market sectors.